

Precast 80

Version 1

pg. 1

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

1.1 Trade Name (as labeled):	Precast 80
Synonyms:	N/A
CAS No:	Mixture
1.2 Product Use:	Liquid release for decorative texturing mats
1.3 Company Name:	SpecChem
Company Address:	1511 Baltimore Ave; Suite 600
Company Address Cont:	Kansas City, MO 64108
Business Phone:	(816) 968-5600
Website:	www.specchemllc.com
1.4 Emergency Telephone Number:	VelocityEHS 1-(800)255-3924 (North America) +1-813-248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)
Date of Last Revision:	April 27, 2015
Date of Current Revision:	July 1, 2018

SECTION 2 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product is a colorless liquid with a root beer fragrance.
Health Hazards: May cause skin, eye, and respiratory system irritation. May be an aspiration hazard.
Flammability Hazards: This product is a combustible liquid with a flash point of ~103°F (39°C).
Reactivity Hazards: None.
Environmental Hazards: The environmental effects of this product have not been investigated, however release may cause long term adverse environmental effects.

US DOT Symbols



EU and GHS Symbols



Signal Word Danger

2.1 EU Labeling and Classification:

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

EU HAZARD CLASSIFICATION OF INGREDIENTS PER DIRECTIVE 1272/2008/EC:

Index Number:

232-489-3 is listed in Annex I 649-345-00-4

Substances not listed either individually or in group entries must be self classified.

Components Contributing to Classification: Stoddard Solvent

Precast 80

Version 1

pg. 2

2.2 Label Elements:

GHS Hazard Classifications:

Flammable Liquids Category 4
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1B
STOT – RE Category 1 (Central Nervous System)

Hazard Statements:

Aspiration Hazard Category 1
H227 Combustible liquid
H340 May cause genetic defects
H350 May cause cancer
H372 Causes damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways

Precautionary Statements:

P280 Wear protective gloves/eye protection/face protection.
P210 Keep away from flames and hot surfaces. No smoking.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Response Statements:

P370+P378 In case of fire: Use dry sand, dry chemical or alcohol resistant foam for extinction.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P301+P310 IF SWALLOWED: Immediately call a POISON Center/doctor.
P331 Do NOT induce vomiting.
P314 Get medical advice/attention if you feel unwell.

Storage Statements:

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal Statements:

P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations..

2.3 Health Hazards or Risks From Exposure:

Symptoms of Overexposure by Route of Exposure:

The most significant routes of overexposure for this product are by contact with skin or eyes. The symptoms of overexposure are described in the following paragraphs.

Acute:

Precast 80

Version 1

pg. 3

Inhalation: May cause respiratory tract irritation. May cause headaches, drowsiness, or dizziness.
 Skin Contact: May cause moderate irritation to skin. Repeated exposure may cause skin dryness or cracking.
 Eye Contact: Vapours and direct contact to the eyes may be irritating.
 Ingestion: May cause lung damage if aspirated.

Chronic: Repeated exposure may cause skin dryness or cracking.

Target Organs:

Acute: Respiratory System
 Chronic: Not known

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	WT%	CAS No.	EINECS No.	Hazard Classification
Stoddard Solvent	90 - 99%	8052-41-3	232-489-3	Carc. 1B, Muta. 1B, STOT RE 1, ASP. Tox. 1
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).				

Note: All WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000

SECTION 4 – FIRST AID MEASURES

4.1 Description of First Aid Measures:

Eye Contact: If product enters the eyes, flush with plenty of water or eye wash solution for several minutes. Remove contacts if present and easy to do. Seek medical attention if irritation persists.

Skin Contact: Wash skin thoroughly with soap and water after handling. Seek medical attention if irritation develops and persists.

Inhalation: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

Ingestion: If product is swallowed, call physician or poison center if you feel unwell. If professional advice is not available, do not induce vomiting. Never induce vomiting or give dilutents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

**Medical Conditions
 Generally Aggravated
 By Exposure:**

Pre-existing skin, respiratory system or eye problems may be aggravated by prolonged contact.

4.2 Symptoms and Effects Both Acute and Delayed: Exposure to skin and respiratory may cause irritation. Contact with the eyes may cause burns. Contact with skin may

Precast 80

Version 1 pg. 4

cause an allergic reaction. Repeated exposure may cause damage to the lungs.

4.3 Recommendations to Physicians: Treat symptoms and eliminate overexposure.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 Fire Extinguishing Materials:

Use the following fire extinguishing materials:

- Water Spray:** No
- Foam:** Yes
- Halon:** Yes
- Carbon Dioxide:** Yes
- Dry Chemical:** Yes
- Other:** Any "C" Class

5.2 Unusual Fire and Explosion Hazards:

Irritating and toxic fumes may be produced at high temperatures. Use of water may result if the formation of a toxic aqueous solution. Do not allow run-off from fire fighting to enter drains or water courses.

Explosive Sensitivity to Mechanical Impact: No
 Explosive Sensitivity to Static Discharge: No

5.3 Special Fire-Fighting Procedures:

- Incipient fire responders should wear eye protection.
- Structural firefighters must wear Self-Contained Breathing Apparatus (SCBA) and full protective equipment.
- Isolate materials not yet involved in the fire and protect personnel.
- Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray.
- If possible, prevent run-off water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING SYSTEM	HMIS RATING SYSTEM HAZARDOUS MATERIAL IDENTIFICATION SYSTEM												
	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #00aaff; color: white;">HEALTH HAZARD (BLUE)</td> <td style="text-align: center; color: white;">2</td> </tr> <tr> <td style="background-color: #ff0000; color: white;">FLAMMABILITY HAZARD (RED)</td> <td style="text-align: center; color: white;">2</td> </tr> <tr> <td style="background-color: #ffff00; color: black;">PHYSICAL HAZARD (YELLOW)</td> <td style="text-align: center; color: black;">0</td> </tr> </table>	HEALTH HAZARD (BLUE)	2	FLAMMABILITY HAZARD (RED)	2	PHYSICAL HAZARD (YELLOW)	0						
HEALTH HAZARD (BLUE)	2												
FLAMMABILITY HAZARD (RED)	2												
PHYSICAL HAZARD (YELLOW)	0												
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4" style="text-align: center;">PROTECTIVE EQUIPMENT</th> </tr> <tr> <th style="width: 25%;">EYES</th> <th style="width: 25%;">RESPIRATORY</th> <th style="width: 25%;">HANDS</th> <th style="width: 25%;">BODY</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"></td> <td style="text-align: center;">See Sect 8</td> <td style="text-align: center;"></td> <td style="text-align: center;">See Sect 8</td> </tr> </tbody> </table>	PROTECTIVE EQUIPMENT				EYES	RESPIRATORY	HANDS	BODY		See Sect 8		See Sect 8
PROTECTIVE EQUIPMENT													
EYES	RESPIRATORY	HANDS	BODY										
	See Sect 8		See Sect 8										
For Routine Industrial Use and Handling Applications Hazard Scale: 0 = Minimum 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic Hazard													

Precast 80

Version 1 pg. 5

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)

6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Use cautious judgment when cleaning up spill. Wear suitable protective clothing, gloves, and eye/face protection.

6.2 Environmental Precautions:

Construct a dike to prevent spreading. Keep out of sewers, storm drains, surface waters, and soils.

6.3 Spill and Leak Response:

Small Spills:

- Collect material via broom or mop. Place in tightly sealed containers for proper disposal.
- Approach spill areas with caution.
- If liquid was introduced, create a dike or trench to contain material.
- Soak up with absorbent material such as clay, sand or other suitable non-reactive material.

Large Spills:

- Place in leak-proof containers. Seal tightly for proper disposal.
- Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada and its Provinces, those of Australia, Japan and EU Member States (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling:

To prevent eye contact under the foreseeable conditions of use, wear appropriate safety eyewear. When handling, do not eat, drink, or smoke. Wash thoroughly after handling.

7.2 Storage and Handling Practices:

Keep away from incompatible materials. Keep container closed when not in use and store in well ventilated area.

7.3 Specific Uses:

Liquid release for decorative texturing mats.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Parameters:

Ingredients	CAS No.	OSHA PEL	NIOSH PEL
Stoddard Solvent	8052-41-3	500 ppm	350 mg/m3

8.2 Exposure Controls:

Ventilation and Engineering Controls:

Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

Precast 80

Version 1

pg. 6

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132), or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

Respiratory Protection:

Maintain airborne contaminant concentrations below guidelines listed above. Use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

Eye Protection:

Safety glasses or goggles are required. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

Hand Protection:

Chemical resistant gloves are required to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards.

Body Protection:

Use body protect appropriate to task being performed. If necessary, refer to appropriate Standards of Canada, or appropriate standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on Basic Physical and Chemical Properties:****Appearance (Physical State and Color):** Colorless liquid**Odor:** Root beer fragrance**Odor Threshold:** No data available**pH:** No data available**Melting/Freezing Point:** No data available**Boiling Point:** No data available**Flash Point:** 153°F (67°C)

Precast 80

Version 1 pg. 7

Evaporation Rate: No data available
Flammability (Solid; Gas): Not applicable
Upper/Lower Flammability or Explosion Limits: No data available
Vapor Pressure (mm Hg @ 20°C (68° F): No data available
Vapor Density: No data available
Relative Density: No data available
Specific Gravity: No data available
Solubility in Water: No data available
Weight per Gallon: No data available
Partition Coefficient (n-octanol/water): No data available
Auto-Ignition Temperature: No data available
Decomposition Temperature: No data available
Viscosity: No data available
9.2 Other Information: No data available

SECTION 10 – STABILITY AND REACTIVITY

<p> 10.1 Reactivity: 10.2 Stability: 10.3 Possibility of Hazardous Reactions: 10.4 Conditions to Avoid: 10.5 Incompatible Substances: 10.6 Hazardous Decomposition Products: </p>	<p> This product is not reactive. Stable under conditions of normal storage and use. Will not occur. Avoid excessive temperatures, exposure to sunlight, sources of ignition. Strong oxidizing agents. Carbon monoxide and dioxide smoke. </p>
--	---

SECTION 11 – TOXICOLOGY INFORMATION

11.1 Information on Toxicological Effects:

Toxicity Data:

Stoddard Solvent	8052-41-3	LD50 Oral – Rat	>5 mg/kg
		LC50 Inhalation – Rat	>5,500 mg/mg3/4h

Suspected Cancer Agent: Ingredients within this product are found on one or more of the following lists: FEDERAL OSHA Z LIST, NTP, IARC, or CAL/OSHA and therefore are considered to be cancer-causing agents by these agencies.
Irritancy: Skin, eye, and respiratory irritant.
Sensitization to the Product: This product is expected to cause skin sensitization.
Germ Cell Mutagenicity: This product does not contain ingredients that are suspected to be a germ cell mutagenic.
Reproductive Toxicity: This product is not expected to be a human reproductive toxicant.

SECTION 12 – ECOLOGICAL INFORMATION

<p> 12.1 Toxicity: 12.2 Persistence and Degradability: </p>	<p> No specific data available on this product. No specific data available on this product. </p>
--	---

Precast 80

Version 1 pg. 8

<p>12.3 Bioaccumulative Potential:</p> <p>12.4 Mobility in Soil:</p> <p>12.5 Results of PBT and vPvB Assessment:</p> <p>12.6 Other Adverse Effects:</p> <p>12.7 Water Endangerment Class:</p>	<p>No specific data available on this product.</p> <p>No specific data available on this product.</p> <p>No specific data available on this product.</p> <p>No data available</p> <p>At present, there are no ecotoxicological assessments for this product.</p>
--	--

SECTION 13 – DISPOSAL CONSIDERATIONS

<p><u>13.1 Waste Treatment Methods:</u></p> <p><u>13.2 EU Waste Code:</u></p>	<p>Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Australia, EU Member States and Japan.</p> <p>Not determined</p>
--	--

SECTION 14 - TRANSPORTATION INFORMATION

14.1 U.S. Department of Transportation (DOT) Shipping Regulations:
This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

UN Identification Number:	UN1993
Proper Shipping Name:	Combustible Liquid, n.o.s. (contains Aromatic Hydrocarbon)
Hazard Class Number and Description:	Class 3 – Combustible Liquid
Packing Group:	III
DOT Label(s) Required:	Combustible
North American Emergency Response Guidebook Number:	128

14.2 Environmental Hazards:

Marine Pollutant:	The components of this product are designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).
<u>14.3 Special Precaution for User:</u>	None

14.4 International Air Transport Association Shipping Information (IATA):

14.5 International Maritime Organization Shipping Information (IMO):

UN Identification Number:	UN1993
Proper Shipping Name:	Flammable Liquid, n.o.s. (contains Aromatic Hydrocarbon)
Hazard Class Number and Description:	Class 3 – Flammable Liquid
Packing Group:	III
EMS-No:	F-E-S-E

Special Notes: The flash point for this material is greater than 100 F (38 C). Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-

Precast 80

Version 1

pg. 9

regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

SECTION 15 – REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations Specific for the Substance or Mixture:

United States Regulations:

U.S. SARA Reporting Requirements:

The components of this product are subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA 311/312:

Acute Health: Yes; Chronic Health: Yes; Fire: Yes; Reactivity; No

U.S. CERCLA Reportable Quantity:

None

U.S. TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory or are exempted from listing.

Other U.S. Federal Regulations:

None known

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):

This product does not contain ingredients on the Proposition 65 Lists.

15.2 Canadian Regulations:

Canadian DSL/NDSL Inventory Status:

Components are DSL Listed, NDSL Listed and/or are exempt from listing

Other Canadian Regulations:

Not applicable

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian WHMIS Classification and Symbols:

This product is Class B2, Flammable Liquid, and D2B, Materials causing other toxic effects, per WHMIS Controlled Product Regulations.



15.3 European Economic Community Information:

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives. See Section 2 for Details.

Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

15.4 Australian Information for Product:

Components of this product are listed on the International Chemical Inventory list.

15.5 Japanese Information for Product:

Precast 80

Version 1

pg. 10

Japanese Minister of International Trade and Industry (MITI) Status: The components of this product are not listed as Class I specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

15.6 International Chemical Inventories:

Listing of the components on individual country Chemical Inventories is as follows:

Australian Inventory of Chemical Substances (AICS): Listed

Korean Existing Chemicals List (ECL): Listed

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed

U.S. TSCA: Listed

SECTION 16 – OTHER INFORMATION

Prepared By: Chris Eigbrett (MSDS to GHS Compliance)

Date of Printing: July 1, 2018

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. SpecChem assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, SpecChem assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET