


SpecSilane 100

Version 1 pg. 1

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

<p>1.1 Trade Name (as labeled): Synonyms: CAS No:</p> <p>1.2 Product Use:</p> <p>1.3 Company Name: Company Address: Company Address Cont: Business Phone: Website:</p> <p>1.4 Emergency Telephone Number:</p> <p style="margin-left: 40px;">Date of Last Revision: Date of Current Revision:</p>	<p>SpecSilane 100 N/A Mixture</p> <p>Penetrating sealer for concrete surfaces</p> <p>SpecChem 1511 Baltimore Ave; Suite 600 Kansas City, MO 64108 (816) 968-5600 www.specchemllc.com</p> <p>VelocityEHS 1-(800)255-3924 (North America) +1-813-248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)</p> <p>July 1, 2018 February 12, 2020</p>
---	--

SECTION 2 – HAZARDS IDENTIFICATION

<p>US DOT Symbols:</p> <p>EU and GHS Symbols:</p> <p>Signal Word:</p> <p>Components Contributing to Classification:</p> <p>2.2 Label Elements: GHS Hazard Classifications:</p> <p>Hazard Statements:</p> <p>Precautionary Statements:</p> <p>Response Statements:</p>	<p>Flammable</p>  <p>Danger</p> <p>Distillates (Petroleum) hydrotreated light, Isobutyl trimethoxysilane, Polydimethylsiloxane</p> <p>Flammable Liquids – Category 3 Aspiration hazard – Category 1 Flammable liquid and vapor. May be fatal if swallowed and enters airways. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion proof electrical, ventilating, lighting and all material-handling equipment. Use only nonsparking tools. Take precautionary measures against static discharge. Keep container tightly closed. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off</p>
--	--

SpecSilane 100

Version 1

pg. 2

Storage Statements:

immediately all contaminated clothing. Rinse skin with water or shower.
 Store locked up. Store in a well-ventilated place. Keep cool.

Disposal Statements:

Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	Percent	CAS No.
Distillates (Petroleum) hydrotreated light	60-90%	64742-47-8
Isobutyl trimethoxysilane	1-20%	18395-30-7
Polydimethylsiloxane	3-15%	63148-62*9

Note: All WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000

SECTION 4 – FIRST AID MEASURES
4.1 Description of First Aid Measures:

- Eye contact :** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation :** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact :** Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion :** Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SpecSilane 100

Version 1

pg. 3

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact :** No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation.
Ingestion : May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact :** No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
dryness
cracking
Ingestion : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 5 – FIRE FIGHTING MEASURES

Fire Extinguishing Materials:

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Do not use water jet.

Specific hazards arising from the chemical: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products : No specific data.

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SpecSilane 100

Version 1

pg. 4

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)

Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental Precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Spill and Leak Response:

Small Spills:

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spills:

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling:

Protective Measures: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

SpecSilane 100

Version 1 pg. 5

Advice on general

Occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe Storage, including any Incompatibilities:

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Parameters:

Ingredients	Exposure Limits
Distillates (petroleum), hydrotreated light	ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours.

Appropriate engineering controls:

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures:

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

SpecSilane 100

Version 1

pg. 6

Eye/Face Protection:

Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

**Skin Protection:
Hand Protection:**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body Protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection:

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SpecSilane 100

Version 1

pg. 7

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES
9.1 Information on Basic Physical and Chemical Properties:
Appearance (Physical State and Color): Colorless liquid

Odor: Mild. Hydrocarbon.

Odor Threshold: No data available

pH: No data available

Melting/Freezing Point: -49°C (-56.2°F)

Boiling Point: 148.89 to 212.78°C (300 to 415°F)

Flash Point: Closed cup: 40°C (104°F) [Tagliabue.]

Evaporation Rate: 0.12 (butyl acetate = 1)

Flammability (Solid; Gas): Not applicable

Upper/Lower Flammability or Explosion Limits: Lower: 0.6% Upper: 5.5%

Vapor Pressure (mm Hg @ 20°C (68° F): 0.21 kPa (1.6 mm Hg) [room temperature]

Vapor Density: 4.5 [Air = 1]

Relative Density: 0.7669

Solubility in Water: 1.5 g/l

Weight per Gallon: No data available

Partition Coefficient (n-octanol/water): No data available

Auto-Ignition Temperature: No data available

Decomposition Temperature: No data available

Viscosity: Kinematic (40°C (104°F)): <0.1 cm²/s (<10 cSt)

9.2 Other Information: No data available

SECTION 10 – STABILITY AND REACTIVITY
10.1 Reactivity:

This product is not reactive.

10.2 Stability:

Stable under conditions of normal storage and use.

10.3 Possibility of Hazardous Reactions:

Will not occur.

10.4 Conditions to Avoid:

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

10.5 Incompatible Substances:

Strong oxidizing agents.

10.6 Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 – TOXICOLOGY INFORMATION
11.1 Information on Toxicological Effects:
Toxicity Data:

Distillates (petroleum), hydrotreated light	64742-47-8	LD50 Oral – Rat	>5,000 mg/kg
		LD50 Dermal – Rabbit	>2,000 mg/kg

Irritation/Corrosion:

Not available

Sensitization:

Not available

SpecSilane 100

Version 1

pg. 8

Mutagenicity: Not available
Carcinogenicity: Not available
Reproductive Toxicity: Not available

Specific target organ toxicity (single exposure):

Name	Category	Route of Exposure	Target organs
Distillates (petroleum), hydrotreated light	Category 3	Not applicable	Narcotic effects

Specific target organ toxicity (repeated exposure): Not available

Aspiration hazard:

Name	Result
Distillates (petroleum), hydrotreated light	Aspiration Hazard – Category1

Information on the likely routes of exposure: Routes of entry anticipated: Oral, Dermal, Inhalation

Potential acute health effects:

Eye Contact: No known significant effects or critical hazards.
Inhalation: No known significant effects or critical hazards.
Skin Contact: Defatting to the skin. May cause skin dryness and irritation.
Ingestion: May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye Contact: No specific data
Inhalation: No specific data
Skin Contact: Adverse symptoms may include the following: irritation, dryness, cracking
Ingestion: Adverse symptoms may include the following: nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short Term Exposure

Potential immediate effects: Not available
Potential delayed effects: Not available

Long Term Exposure

Potential immediate effects: Not available
Potential delayed effects: Not available

Potential Chronic Health effects: Not available

General: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity: No known significant effects or critical hazards.
Mutagenicity: No known significant effects or critical hazards.
Teratogenicity: No known significant effects or critical hazards.
Developmental effects: No known significant effects or critical hazards.

SpecSilane 100

Version 1

pg. 9

Fertility effects

No known significant effects or critical hazards.

Numerical measures of toxicity**Acute toxicity estimates**

Not available

SECTION 12 – ECOLOGICAL INFORMATION
12.1 Toxicity:

Distillates (petroleum), hydrotreated light	LC50 – Fish	2.2 mg/l – 96h
---	-------------	----------------

12.2 Persistence and Degradability:

No specific data available on this product.

12.3 Bioaccumulative Potential:

No specific data available on this product.

12.4 Mobility in Soil:

No specific data available on this product.

12.5 Results of PBT and vPvB Assessment:

No specific data available on this product.

12.6 Other Adverse Effects:

No data available

12.7 Water Endangerment Class:

At present, there are no ecotoxicological assessments for this product.

SECTION 13 – DISPOSAL CONSIDERATIONS
13.1 Waste Treatment Methods:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

13.2 EU Waste Code:

D001 [Flammable]

SECTION 14 - TRANSPORTATION INFORMATION
14.1 U.S. Department of Transportation (DOT) Shipping Regulations:**UN Identification Number:**

UN1263

SpecSilane 100

Version 1

pg. 10

Proper Shipping Name:	PAINT RELATED MATERIAL
Hazard Class Number and Description:	3
Packing Group:	III
DOT Label(s) Required:	None
North American Emergency Response Guidebook Number:	None
<u>14.2 Environmental Hazards:</u>	
Marine Pollutant:	None
<u>14.3 Special Precaution for User:</u>	None
<u>14.4 International Air Transport Association Shipping Information (IATA):</u>	This product is considered as dangerous goods.
<u>14.5 International Maritime Organization Shipping Information (IMO):</u>	
UN Identification Number:	Not regulated
Proper Shipping Name:	None
Hazard Class Number and Description:	None
Packing Group:	None
EMS-No:	None

SECTION 15 – REGULATORY INFORMATION
15.1 Safety, Health and Environmental Regulations Specific for the Substance or Mixture:
United States Regulations:
U.S. SARA Reporting Requirements:

TSCA 8(a) CDR Exempt/Partial exemption: This material is listed or exempted.
 This material is listed or exempted

U.S. SARA 311/312:

Fire Hazard

U.S. CERCLA Reportable Quantity:

Not Applicable

U.S. TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory or are exempted from listing.

Other U.S. Federal Regulations:

None known

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):

This product does not contain ingredients on the Proposition 65 Lists.

15.2 Canadian Regulations:
Canadian DSL/NDSL Inventory Status:

Components are DSL Listed, NDSL Listed and/or are exempt from listing

Other Canadian Regulations:

Not applicable

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian WHMIS Classification and Symbols:

This product is Class D2A, Materials causing other toxic effects, per WHMIS Controlled Product Regulations.

SpecSilane 100

Version 1

pg. 11



15.3 European Economic Community Information:

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives. See Section 2 for Details.

Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

15.4 Australian Information for Product:

Components of this product are listed on the International Chemical Inventory list.

15.5 Japanese Information for Product:

Japanese Minister of International Trade and Industry (MITI) Status: The components of this product are not listed as Class I specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

15.6 International Chemical Inventories:

Listing of the components on individual country Chemical Inventories is as follows:

Australian Inventory of Chemical Substances (AICS): Listed

Korean Existing Chemicals List (ECL): Listed

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed

U.S. TSCA: Listed

SECTION 16 – OTHER INFORMATION

Prepared By: Chris Eigbrett (MSDS to GHS Compliance)

Date of Printing: July 1, 2018

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. SpecChem assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, SpecChem assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET