

## Rapid Hardening/ Polymer-Modified/ Concrete Resurfacer

A one-component, rapid hardening, polymer modified concrete resurfacing mortar for smoothing, resurfacing, rubbing, and restoring concrete surfaces. Final Finish™ offers a unique long pot life but rapid hardening performance on the substrate to minimize waste and labor.



### ✓ Benefits

- Ultra Fine – no sand
- Single Component – Just add water
- Rich smooth consistency
- Long Pot Life
- For Interior or Exterior use

# FINAL FINISH



## Usage

- Offers superior durability for all interior and exterior, horizontal, vertical and overhead concrete applications
- Ideal as a trowel down underlayment and for repairs from a true feather edge up to 1/4"
- Can also be used as a skim patch or trowel down underlayment for horizontal repairs subjected to light traffic



## Packaging

- 15 lb pails
  - 40 lb bags (60 bags per pallet)
- Coverage of 40 lbs: approx 120 sq-ft @ 1/16"

## TYPICAL TEST DATA

Pot Life @ 72°F	Up to 3 hours
<b>Compressive Strength</b>	
7 Days	2,000 psi
28 Days	3,000 psi
<b>Water Requirements (approx. 30% by weight)</b>	
40 lbs of Final Finish™ will require:	11 to 11.5 pints water (1.40 to 1.44 gallons)
Color	Light Gray