

**MAX-A-TACK TTC®**

**MAX A GUARD™**

# Trackless Tack Coat Emulsion

MAX-A-TACK TTC® is an anionic trackless tack coat emulsion that is used primarily as a tack coat. This product can also be diluted 10% with water and used as a fog seal. MAX-A-TACK TTC® is manufactured to meet applicable state specifications.



## ✓ Benefits

- Lower application rate than most conventional tack coats, resulting in application cost savings
- Fast cure time
- Increases bond strength
- Can also be diluted 10% with water and used as a fog seal
- >50% solids



- Usage**
- Asphalt
  - Exterior Surfaces
  - Sidewalks, streets, bridges, etc.

- Standards**
- Zero VOCs
  - U.S. EPA, SCAQMD, CARB and OTC compliant

- Packaging**
- 5 gallon pails (18 liters)
  - 55 gallon drums (208.2 liters)
  - 275 gallon tote (1,041 liters)

## TYPICAL PERFORMANCE DATA

| <u>Specification</u>             | <u>Minimum</u> | <u>Maximum</u> |
|----------------------------------|----------------|----------------|
| Viscosity, seconds (T72)         | 0              | 100            |
| Sieve Test, % (T59)              | 0.00           | 0.10           |
| Residue by Distillation, % (T59) | 50             | -              |
| Oil Distillate, % (T59)          | 0              | 3              |
| Penetration (T49)                | 0              | 40             |