

HYDROPATCH

High Performance Water-Activated Asphalt Cold Patch

DESCRIPTION

HydroPatch provides a high performance and cost-effective solution for permanent repair for asphalt and concrete surfaces. This environmentally friendly, cold-mix, water-activated product sets up rapidly and is traffic-ready immediately. Due to its revolutionary organic renewable additives, **HydroPatch** offers a permanent repair solution, thus eliminating the need for repeated repairs or replacements. It is a weather-friendly product, usable all year round, under any weather condition.

FEATURES / BENEFITS

- Easy to use – Just pour, add water, and tamp
- Durable – As robust as hot mix asphalt
- Fast and resilient – Traffic-ready immediately
- Cost-efficient – Avoids repeated repairs
- Environmentally friendly – Contains NO petroleum-based distillate solvents or cutbacks
- Quickly sealed – Can be sealed immediately after one-hour cure
- Simple – No tack coat required for repairs
- Versatile – No job too big or small - available in 55 lb pails
- Permanent – Prevents repeat repairs of the same pavement defect

APPLICATION

HydroPatch is versatile and can be used for asphalt road patching, concrete road repairs, pothole repairs, drive-ways, walkways, parking lots, utility cuts, manhole repairs, and bridge joints. It is highly beneficial for repair crews, seal coat crews, and for pavement maintenance at schools, airports, hospitals, and other institutional facilities.

Instructions for Use:

1. Remove loose debris and clean the area to be patched.
2. Pour HydroPatch in the hole.
3. Spread and level. If deeper than 2 inches, apply in two layers.
4. Pour water over HydroPatch evenly. Excess water does not damage the material or undermine the repair.
5. Compact into a smooth finish immediately

The service life of HydroPatch is generally on par with ordinary hot-mix asphalt. However, it may vary depending on the volume of traffic and the structural integrity and extent of damage of the surface.



PACKAGING/SHELF LIFE

55 lb pails (36 pails per pallet)

Shelf life is 6 months for properly stored material in pails.

Keep HydroPatch dry, away from moisture during storage and minimize direct sunlight exposure.

LIMITATIONS / PRECAUTIONS

- Keep the container completely sealed prior to use.
- Keep out of the reach of children.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- Wear protective clothing, goggles and avoid skin contact. Can cause skin irritation upon contact. If skin contact occurs, wash immediately with soap and water and seek medical help as needed. If eye contact occurs, flush immediately with clean water and seek medical help as needed.
- Refer to Safety Data Sheet for complete health and safety information prior to using product.
- Turning/steering over the material and objects (treads, high heels, etc.) that can penetrate must be avoided for one hour.

WARRANTY

NOTICE-READ CAREFULLY CONDITIONS OF SALE

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.

TECHNICAL SERVICES

For assistance, contact technical services at:
816-968-5600
www.specchem.com



1511 Baltimore Ave, Suite 600
Kansas City, MO 64108
www.specchem.com 816.968.5600