TECHNICAL DATA SHEET

ORANGE PEEL

Citrus Cleaner – Citrus-Based Solvent Degreaser/Stripper

DESCRIPTION

Orange Peel concentrate is a cost-effective, natural citrus solvent, cleaner and degreaser. Orange Peel is an innovative solution for the toughest industrial applications. Orange Peel will effectively remove grease, grime and other contaminants from architectural concrete and other surfaces.

Orange Peel can also be used to remove asphalt from tools or paving machines and to dissolve/strip many types of carpet and tile cutback adhesives safely and effectively. Standard harsh cleaners and degreasers are made from chlorinated or hydrocarbon solvents that can be hazardous to use and to dispose of.

Orange Peel is VOC compliant with a pleasant citrus odor (check local regulations).

COMPLIANCE/STANDARDS

- VOC compliant, non-etching cleaner/degreaser/stripper

APPLICATION

Coverage: Concentrated Orange Peel is ready to use on tough jobs, or follow the recommended dilution table. Field test to determine the optimal concentration for the specific application. The product will turn white when diluted with water.

Application	Recommended Dilution
Heavy stains, tire marks, cures	No dilution
Cutback adhesives, asphalt paving equipment	No dilution
Industrial dirt/grime/residual tilt-up bond breaker	1 part to 4 parts water
Industrial/institutional warehouse floor, general cleaning	1 part to 5 parts water

Use: Scrape off excess accumulations of grease, grime and contaminants. Apply Orange Peel to the floor or stain either as a concentrate or at the recommended dilution rate. Spread uniformly over the surface and allow the product to penetrate for approximately 5 minutes. Orange Peel's unique blend of emulsifiers and wetting agents allows maximum penetration for effective cleaning.

Scrub the area with a stiff bristle broom or a power floor scrubber. Thoroughly rinse the entire area with clean water. Stubborn stains may require additional treatments.

Stripping acrylic curing/sealing and resin curing compounds will require an undiluted application, keeping the material wet with itself for 20–30 minutes. Then apply water while scrubbing and vacuuming up the residue. Heavy buildup may require additional treatments to completely remove.

PACKAGING

55-gallon drums (208 L)

5-gallon pails (18.9 L)

1-gallon jugs, 4 per case (3.78 L)

1511 Baltimore Ave, Suite 600
Kansas City, MO 64108

www.SpecChem.com
816-968-5600

SHELF LIFE

Store material in the original, tightly closed containers. Do not allow the accumulation of water, dirt or other contaminants. Shelf life of Orange Peel in the original, tightly closed containers is three years from the date of manufacture.

LIMITATIONS

Check local VOC regulations before using. Not VOC compliant in California; use SpecChem Berry Clean in California.

Conduct tests prior to application on various painted surfaces. Orange Peel concentrate may soften, discolor and/or remove some paints. Do not use on resilient tile, rubber or asphalt. Orange Peel is highly concentrated; personal protective equipment should be worn.

DO NOT EXPOSE TO OR APPLY NEAR FIRE OR FLAMES. FOR WELL-VENTILATED OR EXTERIOR USE ONLY.

PRECAUTIONS

DO NOT CUT OR WELD CONTAINER
KEEP AWAY FROM OPEN FLAME
INDUSTRIAL USE ONLY
USE PROTECTIVE GLOVES AND GOGGLES
HARMFUL IF SWALLOWED

Additional precautions, safety and first aid information are contained in the Safety Data Sheet (SDS).

TECHNICAL SERVICES

For assistance, contact Technical Services at 866-791-8700 or 913-371-8700.

24-Hour Emergency Contact: VelocityEHS
1-800-255-3924 (North America)
+1-813-248-0585 (International)
1-300-954-583 (Australia)
0-800-591-6042 (Brazil)
400-120-0751 (China)
000-800-100-4086 (India)
800-099-0731 (Mexico)

MADE IN AMERICA

WARRANTY

NOTICE – READ CAREFULLY

CONDITIONS OF SALE

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.

Revised 09/30/26