TECHNICAL DATA SHEET

SpecChem Xylene

High-Strength Solvent Cleaner

DESCRIPTION

A clear, colorless, flammable, high-strength solvent formulated specifically as a thinner and clean-up material for resin-based compounds. Xylene has a greater solvency strength (KB value) than SpecChem Solvent 100 or mineral spirits.

USES

- For equipment and tool clean-up
- For quicker clean-up of epoxy and urethane on equipment and tools as compared to Aromatic 100
- Troweling aid for epoxy mortars
- Better thinning properties and clean-up material for acrylic and other resin-based curing compounds
- SpecChem Xylene can be used to thin 100% solids epoxy coating systems. Check federal or local maximum allowable VOC laws before thinning.

PACKAGING

55-gallon drums (208.2 L)

5-gallon pails (18.9 L)

1-gallon cans, 6 per case (3.8 L)

SHELF LIFE

When stored in the original, tightly closed container, preventing the accumulation of water, dirt or other contaminants, the shelf life is two years from the date of manufacture.

Store in a cool, ventilated place. Protect material from direct sunlight.

Do not store or handle near an open flame, heat or other sources of ignition.

LIMITATIONS

Caution: Flammable. Contains petroleum distillates. Keep out of reach of children. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, do not induce vomiting; call a physician. If splashed in eyes, wash repeatedly with clean water and call a physician. Keep away from heat, sparks and open flame. Do not pressurize, cut, heat or weld containers.

PRECAUTIONS

Recommended Safety Equipment: Rubber gloves, goggles and, if applied in areas of poor or inadequate ventilation, a Mine Safety Appliances mask and canister:

- Organic vapor mask (No. 457081)
- Organic vapor canister (No. 77705GAM)

Threshold Limit Value: 100 ppm. The ventilation system should be capable of exchanging the total air volume in the application area in 30 minutes or less.

Avoid hazards by following all precautions found in the Safety Data Sheet (SDS), product labels and technical literature. Please read this information prior to using the product.

DO NOT EXPOSE TO OR APPLY NEAR FIRE OR FLAMES. FOR WELL-VENTILATED OR EXTERIOR USE ONLY.

TECHNICAL SERVICES

For assistance, contact Technical Services at 866-791-8700 or 913-371-8700.

1511 Baltimore Ave, Suite 600
Kansas City, MO 64108

www.SpecChem.com
816-968-5600

24-Hour Emergency Contact: VelocityEHS

1-800-255-3924 (North America)

+1-813-248-0585 (International)

1-300-954-583 (Australia)

0-800-591-6042 (Brazil)

400-120-0751 (China)

000-800-100-4086 (India)

800-099-0731 (Mexico)

MADE IN AMERICA

WARRANTY

NOTICE – READ CAREFULLY

CONDITIONS OF SALE

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.

Revised 09/30/26